


# How to find wps pin for hp printer?



To connect your HP printer to Wi-Fi and your router asks for a **WPS PIN**, ☎ + 1 888 688 5458  don't worry. Many HP printers generate a **temporary WPS PIN** that you can find directly from the printer or the HP software.

This guide explains **where to find the WPS PIN on an HP printer** and how to use it correctly.

---

## What Is a WPS PIN on an HP Printer?


A **WPS PIN (Wi-Fi Protected Setup PIN)** is an **8-digit security code** used to connect your HP printer to a wireless network without typing the Wi-Fi password.

 Important: ☎ + 1 888 688 5458 

- The WPS PIN is **temporary** (valid for 5–10 minutes)
  - Not all HP printers support WPS PIN method
- 

## How to Find WPS PIN for HP Printer (Touchscreen Models)

If your HP printer has a touchscreen:

1. Turn ON the printer ☎ + 1 888 688 5458 
2. Tap **Wireless** or **Network Settings**
3. Select **Wi-Fi Protected Setup (WPS)**
4. Choose **WPS PIN**
5. The **8-digit WPS PIN** will appear on the screen

👉 Enter this PIN on your router or computer when prompted.

---

## How to Find WPS PIN for HP Printer (Non-Touchscreen Models)

For printers without a display: ☎ + 1 888 688 5458 OK

1. Press and hold the **Wireless** (📶) button
  2. Press the **Cancel (X)** button at the same time
  3. Hold both for **5 seconds**
  4. The printer enters **WPS PIN mode**
  5. Use HP Smart App or computer to view the PIN
- 

## How to Use WPS PIN to Connect HP Printer to Wi-Fi

1. Log in to your **router's admin page** ☎ + 1 888 688 5458 OK
2. Go to **Wireless** → **WPS**
3. Select **WPS PIN Method**
4. Enter the **HP printer WPS PIN**
5. Click **Connect**

Connection completes within 1–2 minutes.

## Final Thoughts

Finding the **WPS PIN for an HP printer** is simple if your printer supports it ☎ + 1 888 688 5458 OK . You can locate it through the printer screen, HP Smart App, or wireless settings. If WPS isn't available, the HP Smart App offers a faster and more reliable setup method.

